





BLUETOOTH TRANSCIEVER

BLUETOOTH TRANSCEIVER

- BLUETOOTH V4.2 CLASS 2
- STEREO OUT (TO THE STUDIO)
- MONO IN (TO THE CALLER)
- MANUAL OR GPIO CONTROL
- 12V POWER INPUT











The AeroAudio BT1 is a bluetooth receiver and transmitter for connecting bluetooth devices to a broadcast studio. Not only can music be played from, for example, a mobile phone, but the phone can also be used as a telephone link and a conversation can be broadcasted directly through WhatsApp, Skype, telephony or other communication apps. The caller receives the return signal from the studio.

Status LED indicator

The LED will light up when the 12VDC power supply is present and varies in state of standby or connected.

12VDC POWER INPUT

Ratings: 12VDC (9~18 volt) at 250mA. The polarity is not important Power supply is included, options: 115V/USA - 230V/AUS - 230V/EUR - 230V/UK

AUDIO OUT (TO STUDIO)

Stereo left and right output; connect to your equipment with standard XLR cable (XLR 3pin)

- PIN1: Ground (Shield)
- PIN2: Positive (Red)
- PIN3: Negative (Blue)

AUDIO IN (TO CALLER)

Mono input; connect to the studio to the BT1 with standard XLR cable (XLR 3pin)

- PIN1: Ground (Shield)
- PIN2: Positive (Red)

GPIO CONTROL

GPI control to remotely activate or deactivate the transmission link.

GPO output to remotely indicate the transceiver's status



STEENWEG 148C

9810 NAZARETH - BELGIUM

T+32 (0)9 396 76 40

INFO@AEROAUDIO.BE - WWW.AEROAUDIO.BE